


Fusion IR HD –TVI 2M Pancake Camera

Specifications



Features

- Fusion IR HD –TVI 2M Pancake Camera
- 1/3" Progressive scan CMOS Sensor
- HD-TVI (2M 1920×1080P)
- Super IR LED 2EA
- DNR (Digital Noise Reduction)
- Dark Hunter (×32)
- Digital Zoom (×12)
- BLC (Backlight Compensation)
- MIRROR (Horizontal)
- DEFOG
- IP66 weatherproof housing

Model	KB-AV21
Image Sensor	1/3 inch Progressive scan CMOS Sensor
Scanning System	Progressive Image Processing
Effective Pixels	1944 (H) x 1092(V)
Lens	Fixed Mega Pixel Lens(3.6mm, F 1.8)
Min. Illumination	Dark Hunter : 0.0005 Lux, IR LED ON : 0.0Lux
BLC	ON/OFF
Exposure	AUTO / MANUAL
White Balance	ATW(2,000 K ~ 10,000 K)/ MANUAL / PUSH
Day & Night	Mechanical ICR Type
Functions	WDR, FLICKERLESS, DNR, ACE, DEFOG PRIVACY MASK, MIRROR, BLC, MOTION
Sync. System	Internal Sync
Electronic Shutter	1/30(25) ~ 1/30,000
HD Format	TVI Output 1Vp-p, 75ohm
Horizontal Resolution	1920 x 1080P/30fps or 25fps
Analog Video	Analog Composite(1V±0.2Vp-p)
Supply Voltage	12V DC (±10%)
Power Consumption	370mA, 4.5W (Max)
Operating Temperature /Humidity	-10°C ~ 50°C / 30% ~ 80% RH
Storage Temperature / Humidity	-20°C ~ 60°C / 20% ~ 90% RH
IP	IP66

Dimensions

