


KX-C2003N2

2MP H.265 HD Network IR Bullet Camera



- . 1/2.8" 2Megapixel Aptina
- . H.265+ & H.264 dual-stream encoding
- . Max 25/30fps@2M(1920x1080)
- . DWDR, Day/Night(ICR), 3DNR, HLC, BLC
- . Multiple network monitoring: Web viewer, KBiVMS, KBview
- . 3.6mm fixed lens (6mm optional)
- . Max. IR LEDs Length 30m(6mm fixed lens up to 50m)
- . Support Micro SD card, Max 128GB
- . IP67, PoE



Technical Specification

Camera

Image Sensor	1/2.8" 2Megapixel Aptina
Effective Pixels	1920(H)x1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s
Minimum Illumination	0.15Lux/F2.0(Color,1/30s,30IRE) 0.016Lux/F2.0(Color,1/3s,30IRE), 0 Lux/F2.0(IR on)
S/N Ratio	More than 42dB

Camera Features

IR LEDs number	2pcs
Max. IR LEDs Length	3.6mm lens up to 30m (6mm lens up to 40m)
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas

Lens

Focal Length	3.6mm (6mm optional)
Max Aperture	F2.0
Focus Control	Manual
Angle of View	3.6mm H: 90°/ V: 48° 6mm H 55°/ V: 31°
Lens Type	Fixed lens
Mount Type	Board-in Type

Video

Compression	H.265+/H.264/MJPE
Resolution	1080P(1920x1080)/720P(1280x720)/ D1(704x576/704x480)/ CIF(352x288/352x240)
Max Frame Rate	1080P (1 ~ 25/30fps) 720P (1 ~ 25/30fps) D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 16K ~ 8192Kbps H.265+ : 6K~6.4Mbps

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP;TCP;ARP;RTSP;RTP;UDP;RTCP;SMTP;FTP; DHCP;DNS;DDN S;IPv4/v6;SNMP;QoS;UPnP;NT
Compatibility	ONVIF, PSIA, CGI
Max. User Access	20 users
Smart Phone	IOS, Android

Auxiliary Interface

Memory Slot	Micro SD Max 128GB
-------------	--------------------

General

Power Supply	DC12V, PoE (IEEE 802.3af)(Class 0)
Power Consumption	Max 5.5W
Working Environment	-30°C~+60°C
Ingress Protection	IP67
Dimensions	Φ194mm×96mm×89mm
Weight	0.71Kg(with package 0.80kg)

Dimensions (mm/inch)

