

KX-CF2101S

2MP Full-color HDCVI Bullet Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- 24/7 color imaging, Max. 30 fps@1080p
- 20 m illumination distance
- Super Adapt, 130 dB true WDR, 3D NR
- Built-in mic (-A)
- 3.6 mm fixed lens (2.8 mm optional)
- CVI/CVBS/AHD/TVI switchable
- IP67, DC 12 V



Camera																
Image Sensor	1/2.8" CMOS															
Max. Resolution	1920 (H) × 1080 (V)															
Pixel	2MP															
Scanning System	Progressive															
Electronic Shutter Speed	PAL: 1/25 s–1/100,000 s NTSC: 1/30 s–1/100,000 s															
S/N Ratio	> 65 dB															
Min. Illumination	0.001 Lux/F1.6, 30IRE, 0 Lux LED on															
Illumination Distance	20 m (65.6 ft)															
Illuminator On/Off Control	Auto; manual															
Illuminator Number	1															
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90° Rotation: 0°–360°															
Lens																
Lens Type	Fixed lens															
Mount Type	M12															
Focal Length	2.8 mm; 3.6 mm															
Max. Aperture	F1.6															
Field of View	2.8 mm: H: 107°; V: 56°; D: 127° 3.6 mm: H: 86°; V: 46°; D: 101°															
Iris Type	Fixed iris															
Close Focus Distance	2.8 mm: 0.7 m (2.3 ft) 3.6 mm: 1.1 m (3.6 ft)															
DORI Distance	<table border="1"> <thead> <tr> <th>Lens</th> <th>Detect</th> <th>Observe</th> <th>Recognize</th> <th>Identify</th> </tr> </thead> <tbody> <tr> <td>2.8 mm</td> <td>43.9 m (144 ft)</td> <td>17.5 m (57.4 ft)</td> <td>8.8 m (28.9 ft)</td> <td>4.4 m (14.4 ft)</td> </tr> <tr> <td>3.6 mm</td> <td>53.7 m (176.2 ft)</td> <td>21.5 m (70.5 ft)</td> <td>10.7 m (35.1 ft)</td> <td>5.4 m (17.7 ft)</td> </tr> </tbody> </table>	Lens	Detect	Observe	Recognize	Identify	2.8 mm	43.9 m (144 ft)	17.5 m (57.4 ft)	8.8 m (28.9 ft)	4.4 m (14.4 ft)	3.6 mm	53.7 m (176.2 ft)	21.5 m (70.5 ft)	10.7 m (35.1 ft)	5.4 m (17.7 ft)
	Lens	Detect	Observe	Recognize	Identify											
	2.8 mm	43.9 m (144 ft)	17.5 m (57.4 ft)	8.8 m (28.9 ft)	4.4 m (14.4 ft)											
3.6 mm	53.7 m (176.2 ft)	21.5 m (70.5 ft)	10.7 m (35.1 ft)	5.4 m (17.7 ft)												
Video																
Frame Rate	CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD:															

	PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960 × 576H; NTSC: 960 × 480H
Resolution	1080p (1920 × 1080); 960H (960 × 576/960 × 480)
BLC	BLC/WDR/HLC
WDR	130 dB
White Balance	Auto; Area WB
Gain Control	Auto; manual
Noise Reduction	3D NR
Smart Light	Yes
Mirror	Off/On
Privacy Masking	Off/On (8 area, rectangle)
Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Input	One channel built-in mic (-A)
Power	
Power Supply	12 V ±30% DC
Power Consumption	Max 3.3 W (12 V DC, LED on)
Environment	
Operating Temperature	-40 °C to +60 °C (-40 °F to 140 °F); < 95% (non-condensation)
Storage Temperature	-40 °C to +60 °C (-40 °F to 140 °F); < 95% (non-condensation)
Protection Grade	IP67
Structure	
Casing	Metal throughout the whole casing
Camera Dimensions	174.5 mm × 72.3 mm × 70.6 mm (6.87" × 2.85" × 2.78")
Net Weight	0.34 kg (0.75 lb)
Gross Weight	0.45 kg (0.99 lb)

KX-CF2101S

2MP Full-color HDCVI Bullet Camera

Design and specifications are subject to change without notice.
Pictures in the document are for reference only, and the actual product shall prevail.

Dimensions (mm [inch])

