

# KX-DAi4258GPN3

## 4MP 25x Starlight IR Network PTZ Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- 1/2.8" 4Megapixel CMOS.
- Powerful 25x optical zoom.
- Starlight Technology.
- Max. 25/30fps@4MP.
- IR distance up to 150 m.
- Deep-learning-based perimeter protection.
- Auto-tracking 3.0 and IVS.
- PoE+.
- IP67, IK10.
- SMD 4.0
- Quick Pick.



Camera				
Image Sensor	1/2.8" CMOS			
Pixel	4 MP			
Max. Resolution	2560 (H) × 1440 (V)			
ROM	4 GB			
RAM	1 GB			
Electronic Shutter Speed	1s–1/30,000s			
Scanning System	Progressive			
Min. Illumination	0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (IR light on)			
Illumination Distance	150 m (492.13 ft) (IR)			
Illuminator On/Off Control	Zoom Prio; Manual; Auto; Off			
Illuminator Number	4 (IR)			
Lens				
Focal Length	5 mm–125 mm			
Max. Aperture	F1.6–F3.6			
Field of View	H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7°			
Optical Zoom	25x			
Focus Control	Auto; semi-auto; manual			
Close Focus Distance	0.1 m–2 m (0.33 ft–6.6 ft)			
Iris Control	Auto; manual			
DORI Distance	Detect	Observe	Recognize	Identify
	2,500 m (8202.10 ft)	987.5 m (3239.83 ft)	500 m (1640.42 ft)	250 m (820.21 ft)
PTZ				
Pan/Tilt Range	Pan: 0° to 360° endless; Tilt: –15° to +90°, auto flip 180°			

Manual Control Speed	Pan: 0.1°/s–300°/s Tilt: 0.1°/s–200°/s
Preset Speed	Pan: 400°/s; Tilt: 300°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Power-off Memory	Yes
Idle Motion	Pattern;Preset;Scan;Tour
PTZ Protocol	DH-SD Pelco-P/D (Auto recognition)
Intelligence	
IVS (Perimeter Protection)	Tripwire; intrusion; crossing fence detection; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linkage tracking
Face Detection	Supports face detection, capturing snapshots, uploading face snapshots, enhancing face images, and selecting a preferred image among a group of snapshots. Attribute extraction is also supported
Auto Tracking	Yes
SMD	SMD4.0
Quick Pick	With AI NVR, quickly pick up the human/vehicle targets that users are interested in from SMD events
Video	
Video Compression	H.264H;H.264B;Smart H.265+;H.264;H.265;Smart H.264+;MJPEG
Streaming Capability	3 streams
Resolution	4M (2560 × 1440); 3M (2048 × 1536); 3M (2304 × 1296); 1080p (1920 × 1080); 960p (1920 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); CIF (352 × 288/352 × 240); VGA (640 × 480)

# KX-DAi4258GPN3

## 4MP 25x Starlight IR Network PTZ Camera

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

Video Frame Rate	Main stream: 4M/3M/1080p/1.3M/720p @(1-25/30 fps) Sub stream 1: D1/CIF/VGA @ (1-25/30 fps) Sub stream 2: 1080p/1.3M/720p @(1-25/30 fps)
Bit Rate Control	CBR/VBR
Video Bit Rate	H264: 96 kbps-14848 kbps H265: 38 kbps-8960 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Yes
WDR	120 dB
HLC	Yes
White Balance	Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp
Gain Control	Auto; manual
Noise Reduction	2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Image Stabilization	EIS
Defog	Electronic
Digital Zoom	16x
Image Rotation	180°
Privacy Masking	Up to 24 areas can be set, with up to 8 areas in the same view; multiple colors available
S/N Ratio	≥55 dB
<b>Audio</b>	
Audio Compression	PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; G723
<b>Network</b>	
Network Port	RJ-45 (10/100 Base-T)
Network Protocol	FTP; RTMP; IPv6; Bonjour; IPv4; DNS; RTCP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP
Interoperability	CGI; SDK; ONVIF (Profile S&G&T)
Streaming Method	Unicast/Multicast
User/Host	20 (total bandwidth: 64 M)
Storage	Micro SD card (512 GB); FTP/SFTP; NAS
Browser	IE 9 and later versions Chrome 41 and later versions Firefox 50 and later versions Safari 10 and later versions
Management Software	KBiVMS, KBView Plus
Mobile Client	iOS; Android
<b>Port</b>	
Alarm Input	2 (on-off value input: 0-5 VDC)

Alarm Output	1
Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire)
Alarm Linkage	Capture; recording; send email; preset; tour; pattern; alarm digital output; audio
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card status detection; memory space detection
<b>Power</b>	
Power Supply	24 VDC, 2.5 A ± 25% PoE+ (802.3at)
Power Consumption	Basic: 12 W Max.: 21 W (Illuminator and PTZ)
<b>Environment</b>	
Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Humidity	≤95%
Protection	IP67, IK10, TVS 6000 V lightning proof; surge protection; voltage transient protection
<b>Structure</b>	
Product Dimensions	Φ190.0 mm × 332.0 mm (Φ7.48" × 13.07")
Net Weight	4.7 kg (10.36 lb)
Gross Weight	8.0 kg (17.64 lb)
<b>Dimensions (mm[inch])</b>	

