

KX-F16FL

White Strobe Lamp



- Support stroboflash
- Adopt ATMEL AVR high capability MCU
- Adopt advanced steady flowing technique, accuracy and steady current control
- Adopt cree high capability white LED, energy saving and environmental protection
- Support Illuming automatically according to environment brightness, configure the threshold
- Support video synchronization
- Support snapshot synchronization
- Support adjusting frequency of stroboflash
- Support adjusting brightness
- Support RS485
- Support cascading of multi device
- Support flash of exploding
- Support configing parameter by serial port
- Support upgrade by serial port
- Low response time

Technical Specification

Technical Data

Main Processor	ATMEL AVR MCU
LED Lamp Beads	16 crees, White light LED lamp
User Interface	RS485
Parameter Setting	Web/Client
Cascading	Support 4 devices cascading
Video/Stroboflash Synchronization	Support
Snapshot/Stroboflash Synchronization	Support
Remote Control	Support
Pattern of Stroboflash	Active/Passive Mode
Brightness of Stroboflash	Adjustable
Frequency of Stroboflash	50/60/75/90/100/120Hz
Brightness of Environment	Support adjustment 1~6
Recycle Time	≤40us
Best Lighting Distance	18~25 meters

Power,Size,Environment

Power	AC90~285V, Strobe flash Max. 40W
Color Temperature	6500K
Working Temperature	-30 C~+70 C (-40 F ~+158 F)
Working Humidity	10%~95%

Dimensions (mm/inch)

