

KX-FM32

32" FHD Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- Light and cost-effective plastic housing
- 178°H/178°V extra-wide viewing angle for overall viewing performance
- High fidelity digital processing for a brilliant and vivid video
- 8ms fast response time with no image blurring or ghosting
- Support multiple signal inputs such as HDMI, VGA and USB
- Built-in speakers
- Physical button and infrared remote dual control mode
- Low energy consumption, long service life



| Display | | |
|------------------------------------|-------------------------------------|-----------------------|
| Screen Size | 31.5" | |
| Aspect Ratio | 16:9 | |
| Resolution | 1920×1080 (FHD) | |
| Backlight | LED | |
| Brightness/Luminance | 240 cd/m ² | |
| Contrast | 4000:1 | |
| Display Color | 16.7M(8bit) | |
| Viewing Angle(H/V) | 178°(H)/178°(V) | |
| Response time | 8.5ms | |
| Refresh Rate | 60Hz | |
| Signals | | |
| Input | VGA(D-Sub)×1, HDMI×1, USB×1 | |
| Output | Speaker 4W×2 | |
| General | | |
| Power Supply | AC100~240V (+/-10%), 50/60 Hz | |
| Consumption (Standard) | 55W | |
| Consumption (Standby) | ≤0.5W | |
| Type | Internal | |
| Net Weight | 3.9kg (8.6lb) | |
| Gross Weight | 5.1kg (11.2lb) | |
| Bezel Width | 13.9mm (U/R/L), 20.5mm (B) | |
| Wall Mount | 75×75mm (3.0"×3.0") | |
| Dimension without standard (W×H×D) | 731.4×432.6×67.5mm (28.8"×17"×2.7") | |
| Package(W×H×D) | 797×483×108mm (31.4"×19.0"×4.3") | |
| Work Environment | Temperature | 0°C~40°C (32°F~104°F) |
| | Humidity | 10%~85% |

| Accessory | |
|----------------|---|
| Standard | HDMI cable, power cable, remote control, pedestal |
| Optional | Hanging bracket |
| Dimensions(mm) | |

