KBVISION

KX-LM55-F400 55" UHD LED Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

Features:

- · 4K Ultra-HD resolution
- \cdot Suitable for continuous 24/7 operation
- \cdot 9.5ms response time for no motion blur, judder or ghosting
- · 1.07B colors, for a realistic and immersive visual experience
- · High fidelity digital processing for a brilliant and vivid video
- \cdot 178°/178° extra-wide viewing angle for overall viewing performance
- · Professional thermal design to extend equipment lifespan



Technical Specification

| Display | |
|----------------------|----------------------------|
| Screen Size | 55" |
| Aspect Ratio | 16:9 |
| Resolution | 3840×2160 (UHD) |
| Backlight | LED |
| Brightness/Luminance | 380cd/m² |
| Contrast Ratio | 5000:1 |
| Display Color | 1.07G(8Bit+FRC) |
| Viewing Angle(H/V) | 178°(H)/178°(V) |
| Response Time | 9.5ms |
| Refresh Rate | 60Hz |
| Signals | |
| Input | HDMI ×3, USB ×1 |
| Output | Speaker×2 6W ,Audio out×1 |
| General | |
| Power Supply | AC100~240V , 2.5A,50/60 Hz |

| Consumption (Standard) | 150W | | |
|--------------------------------|---|----------|--|
| Consumption (Standby) | ≤0.5W | | |
| Net Weight | 11.7KG | | |
| Gross Weight | 15.7KG | | |
| VESA | 400×200mm | | |
| Dimension without base (W×H×D) | 1236.0×715×68.3mm (48.7"×28.1"×2.7") | | |
| Package(W×H×D) | 1339×813×148mm (52.7"×32"×5.8") | | |
| Work Environment | Temperature | 0°C~40°C | |
| work Environment | Humidity | 10%~85% | |
| Accessory | | | |
| Standard | power cable, remote control, Pedestal, HDMI cable | | |
| Optional | hanging bracket | | |
| | | | |



KBVISION

KX-LM55-F400 55" UHD LED Monitor

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.

Dimensions(mm)





