

KX-VDP11GWN

Wi-Fi Villa Door Station

Design and specifications are subject to change without notice. Pictures in the document are for reference only, and the actual product shall prevail.



- Ultra slim design.
- PC and ABS material make it ideal for indoor and outdoor use.
- 1/2.8" 2-MP HD CMOS camera.
- Offers two-way video call with indoor monitors.
- Video and voice messages from visitors can be checked on the indoor monitor.
- Video call and unlocking through app.
- IR illumination and auto WDR.
- Wi-Fi connection.
- IP65 rated.
- H.264 and H.265.
- Unlock with IC card.
- PoE power supply



System	
Main Processor	Embedded Processor
Button Type	Mechanical
Interoperability	ONVIF; CGI
Network Protocol	RTSP; DNS; P2P; UPnP; RTP; RTMP; SIP; SSH; HTTP/HTTPS; ONVIF
Basic	
Camera	1/2.8" CMOS 2-MP HD camera
Field of View	H: 110°; V: 62°; D: 133°
WDR	120 dB
Noise Reduction	3D NR; 2D NR
Video Compression	H.264; H.265
Video Resolution	Main stream: 720p, WVGA, D1, and CIF ; Sub stream: 1080p, WVGA, D1, QVGA, and CIF
Video Frame Rate	PAL: 25 fps NTSC: 30 fps
Video Bit Rate	768 kbps–8 Mbps
Light Compensation	Auto IR
Day/Night	Auto (ICR)/Color/B/W; Color/B/W
Audio Compression	G.711a; G.711u; PCM
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression/digital noise reduction; Echo suppression; Digital noise reduction
Audio Bit Rate	16 kHz, 16 bit
Function	
Communication Mode	Full digital

Unlock Mode	Card; app; indoor monitor
Card Type	IC card
Auto Snapshot	Yes (SD card is inserted in the indoor monitor or door station)
Leave Videos	Yes (SD card inserted in VTH/VTO is needed)
Web Configuration	Yes
Wi-Fi	Yes
Wireless Standard	IEEE 802.11b; IEEE 802.11g; IEEE 802.11n
Wireless Frequency Range	2.4 GHz
Storage	Micro SD card (max. 256 GB)
Performance	
Card Reading Distance	0 cm–3 cm (0"–1.18")
Issue Card Locally	Yes
Casing	PC+ABS
Capacity	
Card Capacity	3000
Port	
Exit Button	1
Door Status Detection	1
Lock Control	1
Network Port	1 × RJ-45 10/100 Mbps Ethernet port
Alarm	
Tamper Alarm	Yes
General	
Appearance color	Light grey
Power Supply	12–33 VDC, 1 A ; Standard PoE

KX-VDP11GWN

Wi-Fi Villa Door Station

Design and specifications are subject to change without notice.
Pictures in the document are for reference only, and the actual product shall prevail.

Power Adapter	Optional
Installation	Surface Mount
Accessory	Included: Alarm power ribbon cable, rain cover
Product Dimensions	160 mm × 50 mm × 30 mm (6.30" × 1.97" × 1.18")
Protection	IP65
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Altitude	0 m–3,000 m (0 ft–9,842.51 ft)
Power Consumption	≤ 3.5 W (standby), ≤ 6 W (working)
Gross Weight	0.4 kg (0.88 lb)
Net Weight	0.18 kg (0.40 lb)

Dimensions (mm[inch])

